



ARICUP

FLEXIBLE HIGH SPEED SLEEVING MACHINE FOR INDIVIDUAL PRODUCTS

Flexibility

Automatic size changeover, below 2 minutes (grouping, height).

Packs grouped in one layer : x2, x3, x4, x6, x8.

Packs grouped in two layers : x2, x4, x6, x8.

Width and height adjustment, optional (for various product shapes and sizes).

Processing rate

From 10,000 to 60,000 products per hour. Up to 280 packs per minute.



Complete end of lines

A full range of integrated or separate peripheral equipment is provided enabling the construction of full packaging lines to handle all product flow control functions upstream and downstream from sleever



Technical characteristics

Packs glued on the bottom.

Ergonomics and accessibility studied for the operator.

Continuous servo drive system.

Speed varies with product feed rate.

Stainless steel machine, fully washable with mechanical parts separated from product packaging section, and water proof electrical cables.

Continuous rotary feeder.

Symmetrical version existing.

(i.e. accumulation conveyors, converger, mixer, orienter, coder, divider, case packer, palletizer).

Options

Leaflet, gadget, straw applicator.

Operator graphic terminal for production, size changeovers and maintenance assistance.

Integrated divider.

Inkjet or laser coder integration.

Gussets system for products blocking.

