



PACK LINE Ltd

Packaging Machines Industries

PAO

Line of membrane cutting and sealing from the roll machines

Output: Semi-Automatic models –
up to 12 cycles per minute
Fully-Automatic models –
up to 20 cycles per minute


The models customized for the specific requirements of each project, are cost-performance efficient and friendly for use machines.

Machines can be designed to work with several containers sizes & shapes using easy handled exchange sets
Temper evident membrane is cut directly from a roll.
Multi-layer film can be used to prolong shelf life of some products.

MAP is available for reducing oxygen level in the sealed container.

PAO is used as a sealing device on Pack Line other pre-formed containers filling & sealing machines.



CE  3A/FDA/CE APPROVED

 Member of
FPM&SA



PACK LINE CORP.

• **Head Office**
22900 Miles Rd., Cleveland,
OH 44128
Phone: 212-564-0664
Fax: 973-529-0224
info@packlinecorp.com

• **West coast office:**
1588 Arrow Hwy, Suite D
P. O. Box 7686
La Verne, CA 91750
Direct: 909-374-4562
Office: 909-392-8000
Fax: 707-221-2465
amir@packlinewest.com
www.packlinewest.com

• **East Cost Office**
339 East 81st Street #3D
New York, NY 10028
Phone: 212-372-7669
Fax: 212-401-4770
eran@packlinecorp.com

• **PACK LINE- AUSTRALIA**
1 Merchant Avenue, Thomastown
3074,
Melbourne, Victoria Australia
Phone: +61-3-9466-1470
Fax: +61-3-9466-1471
mzelligman@bigpond.com

• **CANADA - NUSPARK**
Phone: +1 416 663 7071 ext 325
Fax: +1 416-663-0223
melent@nuspark.com ;
tchen@nuspark.com

• **GREECE - EUROPACK**
Industrial Solutions S.A.
Phone: +30-210-96-07-102
Fax: +30-210-96-00-590

• **RUSSIA**
Regional office:

• **THE NETHERLANDS**
DUTCHPACK INTER. B. V.
PHONE: +31-30-251-88-80
Fax: +31-30-251-65-26
maarten.twigtdutchpack.nl

• **UK - LIBERTY PROCESS LIMITED**
Phone: +44 845 0940197
Fax: +44 1925 499519
davidbodilly@libertyprocess.co.uk

• **UKRAINE**
Kiev
Phone/Fax: +380 44 4921696 /97
equip@polymer.in.ua
Donetsk
Phone: +380-62-3122979
Fax: +380-62-3122479
equip@polymer.dn.ua

• **UZBEKISTAN**
Tashkent
Phone: +998-712-567879
+998-97-1307931
Fax: +998-712-567879
mishael@packline.com

PAO

Line of membrane cutting and sealing from the roll machines

List of available features and technical data:

- User friendly sealing system with high quality result
- Cuts and seals directly from the roll.
- Semi-Automatic or automatic models depended on the required output.
- A film is automatically advanced and the waste is rewind.
- Easy exchange for different containers sizes.
- High safety standards.
- All the product contact parts are stainless steel.

The machine is constructed of stainless steel, anodized aluminum and plastic all of which conform to EEC, 3A, FDA standards for food grade materials.

Options:

- Modified Atmosphere System. Residual oxygen level up to 0.3 - 0.4%.
- A film marking detection.
- Stamp coding directly on the film.

PAO is used as a sealing device on other Fully Automatic filling and sealing machines. Output up to 240 PPM.

Technical data:

Power supply	230 V, 50 Hz	110Vx3 phase, 220 V / 60 Hz
Power usage	2 kW	2.6 Hp
Compressed air consumption	200 L/min	11 CFM
Pneumatic feeding	6-8 Bar	90-120 PSI
Length	1200 mm	47 inch
Width	800 mm	31 inch
Height	1600 mm	63 inch
Net weight	150 kg	330 Lb

