

TSM-D

Tunnel Metal Detector for industrial use



PROBE

ELECTRONIC CONTROL UNIT

HIGH IMMUNITY
TO ENVIRONMENTAL
INTERFERENCE



- Detection of both magnetic and non-magnetic metals
- High immunity to environmental interference
- Installed without cutting conveyor belt
- Digital Programming
- Very high reliability
- IP65 main unit and probe



Tel. +39 0575 4181 Fax +39 0575 418296 qa-detectors@ceia-spa.com

www.ceia.net

TSM-D

TUNNEL METAL DETECTOR FOR INDUSTRIAL USE

The CEIA TSM-D digital Metal Detector is suitable for intercepting magnetic and non-magnetic metal fragments of medium to large dimensions in industrial, textile, chemical, mining, foodstuffs and other products, both for quality control and machinery protection

The product to be inspected is carried on a conveyor belt through the Detector Probe, which is connected to the Electronic Control Unit.

The TSM-D Metal Detector probe unit can be opened up, thereby allowing installation on conveyor belts without cutting them.

Detection sensitivity and other operational settings can be pre-selected digitally using function keys and alphanumeric display.

The TSM-D Metal Detector features extremely robust construction, which allows its installation in difficult environments, both inside and outside, without reduction in its operational features.

Digital processing of signals guarantees the highest immunity to external electromagnetic interference.

The TSM-D Metal Detector is tested to conform to Electrical Safety and Electromagnetic Compatibility standards required for the CE mark.


Specifications

DETECTION FUNCTIONS	Adjustable sensitivity
	Interception speed programmable according to applications (2 to 250 m/min)
	Digital programming with alphanumeric display
	Visual and acoustical indicator
	Built-in self-diagnosis system
INPUTS / OUTPUTS	Built-in settings memory without backup battery
	Programmable Alarm Relay: rating 250Vac, 2.5A
	Encoder/Reset Input
POWER SUPPLY	Standard bluetooth connectivity
	100-240 Vac, 50/60 Hz, 1.5A max
ENVIRONMENTAL REQUIREMENTS	Operating temperature: -10 to +55 °C
	Relative humidity: 0 -95% (without condensation)


APPLICATIONS	Product Quality Control and protection of machinery in the following industries: > Textiles > Concrete > Timber > Chemicals > Mining > Paper > Foodstuffs > Clay
CERTIFICATION AND CONFORMITY	Conforms and is tested to European standards required for the CE mark Complies with EC regulations and international standards relating to electrical safety and electromagnetic compatibility
OTHER	Dimensions of main unit and probe: see drawing and table Length of cable connecting main unit and probe: standard 3m, others on request Conforms and is tested to European Standards required for the CE mark

Dimensions

PROBE



ELECTRONIC CONTROL UNIT



W	500 ÷ 1500 in 100 mm increments	Dimensions of standard models (mm)
H	200 ÷ 700 in 50 mm increments	Other sizes on request



COSTRUZIONI ELETTRONICHE INDUSTRIALI AUTOMATISMI

Zona Ind.le 54/G, 52041 Vicinaggio - Arezzo (ITALY)

Phone: +39 0575 4181 Fax: +39 0575 418296 E-mail: qa-detectors@ceia-spa.com

DP014K0001v1000UK

www.ceia.net

CEIA reserves the right to make changes, at any moment and without notice, to the models (including programming), their accessories and options, to the prices and conditions of sale