

YOUR BEST PARTNER IN PACKAGING

Vertical Form Fill Seal (VFFS) machine with reduced footprint.
The ILAPAK Vegatronic 500 inclined is a high-quality entry-level automatic intermittent bagger ideal for a large number of applications which require a gentle product transfer.






TECHNICAL SPECIFICATIONS

	S	P	SP
Machine Speed	70 cpm	70 cpm	70 cpm
Bag Size			
WIDTH MIN	50mm-2.0"	50mm-2.0"	50mm-2.0"
WIDTH MAX	270/280*mm-10.6/11.0"	260/270*mm-10.2/10.6"	Same as per S or P
LENGTH	330mm-13.0"	330mm-13.0"	330mm-13.0"
GREATER LENGTH FEASIBLE ON REQUEST			
Wrapping Materials	Heat sealable materials, such as polypropylene, barrier films, laminates, as well as polyethylene films.		
Film reel Dimensions			
REEL WIDTH MAN	580mm-22.8"	580mm-22.8"	580mm-22.8"
REEL OUTER Ø MAX	400mm-15.7"	400mm-15.7"	400mm-15.7"
REEL CORE Ø MAX	76mm-3.0"	76mm-3.0"	76mm-3.0"
Film Reel Max Weight	100kg-220lbs	100kg-220lbs	100kg-220lbs
Sealing System	Brushless motor driven horizontal sealing jaws-pneumatic vertical seal bar.		
	Standard heat-seal jaws and vertical seal bar	Ilaseal sealing system	Both S & P system
Electronic Platform	PLC Omron for USA & Canada, in particular Allen Bradley platform available		
Program Memory	40 programs		
HMI	5" monocolour touch screen		
Power Req. OPTIONAL EXCLUDED	AC 400 V+/-5%, 3 phase, neutral, 50/60Hz, 3.3kW, 5A		
Compressed Air	AC 400 V+/-5%, 3 phase, neutral, 50/60Hz, 3.3kW, 5A	500-900NI/min, 7 bar-101.5 psi	Same as per S or P
Machine Handing	Right hand version, left hand version *		
Machine Dimensions	(Width x Depth x Height) 1089 x 1992 x 1728 mm - 42.9" x 78.4" x 68"		
Machine Weight	Approx. 650kg – 1433lbs		
Machine finish	Electrostatic epoxy powder coating- Stainless steel*		

* optional

MAIN FEATURES
BENEFITS

Unbeatable entry level design	▶	Competitive Price
Compact footprint	▶	Reduced cost for floor space
Gentle product transfer	▶	Minimum product breakage/damage
Omron PLC control platform (Allen Bradley and Siemens also available)	▶	Worldwide commercially available components Easy maintenance High reliability components
Servo assisted sealing jaws	▶	Fast speed applications with optimized machine cycle
Easy integration with many dosing systems	▶	Can easily run with weighing, counting and volumetric feeding systems



All measurements not specified in inches are given in millimeters. Please discuss your needs with our local representative to configure these machines to your product's specific requirements. These specifications are not binding. We reserve that right to change them without prior notice.

Discover more about us, visit:

www.ilapak.com